

# Jennuflex

## FOAM EXPANSION JOINT FILLER

### DESCRIPTION

- Superior-grade polyethylene expansion joint with unicellular, or closed cell, structure to prevent moisture absorption and heat transfer
- Tough, compressible foam with superior recovery

### ADVANTAGES

- Installs easily and quickly
- Less expensive than conventional joint fillers
- Extremely low moisture absorption
- Resistant to most oils, chemicals, ozone and weathering
- Lightweight, yet structurally strong
- Resilient - readily accepts joint movement
- Nonimpregnated, nonstaining and nonbleeding
- Inert and compatible with cold applied sealants
- No bond breaker needed - sealants do not adhere
- Easy to cut
- Effective substitute for cane fiber

### USES

- All concrete paving work
- Concrete highways, airport runways and streets
- Between adjacent constructions, roadways and buildings
- Abutments, retaining walls, piers and other plain or reinforced concrete structures

MATERIAL PROPERTIES	NOMINAL 1/2" JENNUFLEX
Cell Structure	Closed Cell
Color	Charcoal
Density (lb./cu.ft.)	1.8 lb. to 2.0 lb.
Compression Resistance (psi) 50% Deflection	10
Compression Set ASTM-D-1564	10%
Weatherometer (Carbon Arc) 5,000 hr.	No effect
Compatible Backup For Sealants	All

### SIZES

- 1/2" thick
- 125 ft. per roll
- Available in 4" and 6" widths

### APPLICATION

- Position Jennuflex so it does not protrude above the surface.
- For best results, a minimum of 1/2" should be provided from surface of concrete to top of filler if sealant will be used to seal off joint.

### LIMITED WARRANTY

Every reasonable effort is made to apply exacting standards in manufacturing Jennuflex and in the information we issue concerning it and its use. We will, at our election, replace or refund the purchase price if proven defective. Satisfactory results depend not only on quality products, but also on many factors beyond our control. Therefore, except for such replacement or refund, *Brett Admixtures makes no*

*warranty or guarantee, express or implied, including warranties of fitness or merchantability, and Brett Admixtures shall have no other liability with respect thereto. User shall determine the suitability of Jennuflex for the intended use and assume all risks and liability in connection therewith. Any authorized change in printed recommendations concerning the use of Jennuflex must bear the signature of the director of Brett Admixtures.*